

# 24-PoE (10/100/1000Mbps) + 4-SFP slots (1G/10G)



- ✦ PoE 24-Port + 1G/10G SFP 4-Slot
- ✦ Management : Console, Telnet, SSH, SNMP, HTTP
- ✦ IPv4 and IPv6 support
- ✦ IEEE 802.1d & IEEE 802.1w Rapid Spanning Tree
- ✦ Port Mirroring for Network error and Traffic Analysis
- ✦ IEEE 802.1x User Authentication for Network Security

## Specification

Technology	- Standard	IEEE 802.3ae 10 Gigabit Ethernet IEEE 802.1Q VLAN Tagging IEEE802.3u 100Base-TX/100Base-FX IEEE 802.1w Rapid Spanning tree protocol IEEE 802.3 at/af Power Over Ethernet	IEEE 802.3z Gigabit SX/LX IEEE 802.1x Port Authentication Network Control IEEE 802.3ab Gigabit 1000T IEEE 802.1p Class of Service
	- RJ45 Ports	10/100/1000Mbps PoE 24-Port, Auto-Negotiation, Auto MDI-X	
Interface	- Fiber Ports	1G/10G SFP+ 4Slots	
	- PoE Power	400W	
Performance	- Basic Performance	SWITCH FABRIC : 128Gbps ADDRESS TABLE : 16K entries	THROUGHPUT : 95.2Mpps@64Bytes
	- Feature	VLAN · 4K Active VLAN, QinQ, GVRP, Private VLAN · Spanning Tree 802.1D (STP), 802.1W (RSTP) and 802.1S (MSTP) · Loopback protection and port isolation · Static/LACP link aggregation, LLDP · EAPS and ERPS · IGMP v1/v2/v3, IGMP Snooping, IGMP Fast Leave · QoS, IEEE 802.1x and RADIUS, MAB	
Environmental	- Temperature	Operating: 0°C ~ 45°C, Storage: -40°C ~ 70°C	
	- Humidity	10 ~ 90% (Non-condensing)	
Input Voltage		100~240VAC, 50/60Hz	
Dimensions		440mm(W) x 330mm(D) x 44.5mm(H), 1U	

## Ordering Information

Model Name	Description
SFC4200HP	10/100/1000Mbps PoE 24-Port + 1G/10G SFP+ 4-Slot
SFP-SX	SFP (1.25Gbps), Multi-mode, Transmission distance: 220/550m, 850nm, LC connector
SFP-LX	SFP (1.25Gbps), Single-mode, Transmission distance: 20km, 1310nm, LC connector
SFP+10G-LR	SFP (10.31Gbps), Single-mode, Transmission distance: 10km, LC connector