

PoE 24-Ports Gigabit Optical Switch

PoE 10/100/1000Mbps TP 24-Ports + SFP 2-Slots



- 10/100/1000Mbps TP 24-Ports PoE (802.3at)
- IEEE 802.3at PoE 15.4W 24-Ports (Max. 380W)
- 24-Ports 15.4W simultaneous, 12-Ports 30.8W simultaneous
- 19"Rack mountable
- 100~240VAC Input Power
- 8K MAC Address
- Full-duplex mode IEEE802.3x flow control
- 9216 bytes jumbo frame packet wireless transmission
- 1000Mbps SFP 2-Slots

Specifications

Technology	Standard	IEEE 802.3 10Base-Tx IEEE 802.3u 100Base-TX/100Base-FX IEEE 802.3ab Gigabit 1000T IEEE 802.3at Power over Ethernet IEEE 802.3af Power over Ethernet
Interface	RJ45 Port	10/100/1000Base-T(X) Auto-negotiation, Auto MDI-X UTP/STP Cat. 3,4,5 Cable EIA/TIA-568 100-ohm(100m)
	Fiber Port	SFP 2-Slots, 1000Base-SX/LX SFP
	LED Indication	Power, FD, Link/Act, Speed, PoE
Performance	Back Plane	Switch Fabric 52Gbps, 8K MAC Address table, Jumbo Frame 9.6Kbytes
	PoE	12-Ports : 30.8watt 24-Ports : 15.4watt Max. 380watt
Operating Environment	Temperature	Operating: 0°C ~ 45°C, Storage: -40°C ~ 70°C
	Humidity	10 ~ 90% (Non-condensing)
Power Supply		100~240VAC, 50/60Hz, 400W internal power
Dimension		440mm(W) x 208mm(D) x 44mm(H)

Ordering Information

Model Type	Specification
SFC524HP	10/100/1000Mbps TP 24-Ports PoE(802.3at) + SFP 2-Slots
SFP-SX	SFP(1.25Gbps) module, Multi-mode, Transmission Distance 220/550m, 850nm, LC Connector
SFP-LX20	SFP(1.25Gbps) module, Single-mode, Transmission Distance 20Km, 1310nm, LC Connector