

100Mbps Fiber Optic Ethernet Converter

10/100Mbps-TX to 100Mbps-FX Fast Ethernet Converter, Single-mode 40km



SFC200-SCS40

- Converts TP (10/100Mbps) to Fiber Optic (100Mbps-FX) for Long distance Transmission
- Network Component for Long distance & Noise Solution, Optical LAN, FA, Internet Network, FTTH etc.
- 10/100Mbps Throughput, Auto Negotiation
- TP Cable Auto MDI-X
- LLCF(Link Loss Carry Forward)
- LED Indication for Auto Negotiation and Connection Status
- 10/100Mbps, Full/Half-duplex Manual Operation (DIP Switch)

Specifications

Technology	Standard	IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX/100Base-FX
Interface	RJ45 Ports	1-Port 10/100Mbps TP, Auto-Negotiation, Auto MDI/MDI-X TP/STP Cat. 3, 4, 5, 6 Cable EIA/TIA-568 100-ohm(100m)
	Fiber Ports	1-Port 100Mbps (ST/SC connector) Multi-mode : 62.5/125 μ m (2km), Single-mode : 9/125 μ m(40km)
	LED Indicators	Per unit : Power Per port(TX) : Link, Activity, FDX/HDX, speed Per port(FX) : Link, Activity
	Dip Switch	Internal, Auto-Negotiation, 10/100Mbps, Full/Half Duplex, LLCF on/off
Performance	Data transfer	100Mbps
Operating Environment	Temperature	Operation: 0°C ~ 60°C, Storage: -20°C ~80°C
	Humidity	5 ~ 95% (Non-condensing)
	Power consumption	3.3W
	Installation	Stand alone, Center mount module type
Input Voltage		DC 5V 2A SMPS Adapter
Dimensions		Stand alone : 71mm(W) x 94mm(D) x 26mm(H) Built-in Power Type : 118mm(W) x 184mm(D) x 34mm(H)

Ordering Information

Model Name	Description
SFC200-SCS40	10/100Mbps-TX to 100Mbps-FX Fast Ethernet Converter, Single-mode 40km, 1310nm
SFC200-SCS40/I	10/100Mbps-TX to 100Mbps-FX Fast Ethernet Converter, Single-mode 40km, 1310nm, AC Built-in