

100Mbps Fiber Optic Converter Center

12-slots Dual Power 100M Fiber Optic Center

19 inch Standard Rack, 2U size, SFC200 series Fiber Optic Converter Center, 12 Slots



SFC-CENTER/12D

- Standard 19" Rack Mounting Fiber Optic Center
- 16-slot mounting of Fiber Optic Converter
- AC Dual Power Support
- 12 Slot unit, 2 Power Supply
- 12 Slot Chassis for SFC200 series

Specification

Standard	- Standard	19 inch standard Rack, 2U size
Interface	- RJ45 Port	10/100Mbps, Auto MDI/MDI-X UTP Cat3~6Cable EIA/TIA-568 100-OHM(Transmission distance 100M)
	- Fiber Port	100Mbps: 1-port, 100Base-FX (SC connector) Multi-mode: 62.5/125 μ m(220m) Single-mode:9/125 μ m(~100km)
	- LED Indication	Power A. Power B
Operation Environment	- Temperature Range	Operation: - 0°C ~ 60°C , Storage: - 20°C ~ 80°C
	- Humidity	5 ~ 95% (Non-condensing)
	- Installation	19" RACK mount (2U)
Input Power		110VAC or 220VAC, 50/60Hz, Power redundant(Optional)
Dimension		440.8mm(W) x 250mm(D) x 89mm(H)

Ordering Guide

Model Type	Specification
SFC CENTER/12	12 Slot unit, 1Power Supply, SFC200
SFC CENTER/12D	12 Slot unit, 2Power Supply, SFC200, Dual Power