

10/100/1000Mbps 24-Port Giga Ethernet Optical Switch

10/100/1000Mbps TP 24-Port + 1000Mbps SFP 2-Slot



SOLTECH-2600

- 10/100/1000Mbps TP 24-port
- Full-duplex mode IEEE 802.3x flow control
- 9216 bytes jumbo frame packet wire transmission
- 1000Mbps SFP 2-slot
- Provide Diagnostic LED Indications
- Auto MDI-X tport and Auto-Negotiation
- Internal power supply
- 19" RACK type

Specification

Technology	- Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3ab 1000Base-T IEEE 802.3az
Interface	- Network Cable	TP category 5, 5e cable(Max. 100m)
	- RJ45 Port	10/100/1000Mbps TP 24-port, Auto-Negotiation, Auto MDI-X
	- Fiber Port	1000Mbps SFP 2-slot (LC Connector Type) Multi mode : 62.5/125 μ m(220m), Single mode : 9/125 μ m(~100km)
	- LED Display	Link/Act : Green, 1000Mbps : Green, SFP : Green, Power : Green
Performance	- Transfer Method	Store-and-Forward
	- Switching Capacity	52G
	- MAC Address	16K Address table
	- Forward Rate	10Mbps : 14880pps 100Mbps : 148800pps 1000Mbps : 1488000pps
	- Power Consumption	Max. 20Watt
Operating Environment	- Temperature	Operating: 0°C ~ 40°C, Storage: -40°C ~ 70°C
	- Humidity	5 ~ 90% (Non-condensing)
Power Supply		AC100~240VAC, 50/60Hz(Internal Power Supply)
Dimension		440mm(W) x 205mm(D) x 44mm(H)

Ordering Information

Model	Specification
SOLTECH-2600	10/100/1000Mbps TP 24-port + 1000Mbps SFP 2-slot, Unmanaged Gigabit Ethernet Switch
SFP-SX	SFP(1.25Gbps) module, Multi-mode, Transmission distance 220/550m, 850nm, LC Connector
SFP-LX	SFP(1.25Gbps) module, Single-mode, Transmission distance 20Km, 1310nm, LC Connector