


SFC 9100HP

24-Port PoE Optical Switch

24-Port Gigabit PoE + 4-Port 1G SFP
Managed Switch



Properties

- UTP 24-Port PoE(380W) + SFP 1G 4-Slot Management Switch
- Flexible Ethernet Network Configuration (G.8032 ERPS, STP/RSTP/MSTP)
- Various Security Control (IEEE802.1x, MAC Authentication, Complex Authentication)
- Convenient Operation & Maintenance (CLI, SSH2, SNMP v1/v2/v3, RMON, GVRP, WEB)
- Stacking (Logical Management, Bandwidth Expansion)
- Network Traffic Analysis (Mirroring, sflow)

Specification

Standard	
Standard	10Base-T: UTP category 3, 4, 5 cable(maximum 100m) 100Base-Tx:UTP category 5, 5e cable(maximum 100m) 1000Base-T: UTP category 5e, 6 cable(maximum 100m) 1000Base-X: MMF, SMF
Interface	
RJ45	24 x 10/100/1000Mbps ports(PoE 380W)
Fiber	4 x 1000 Mbps
LED	PWR(Power), STS(Status), MST(Stack), SPEED, PoE, Link/Activity
Switching capacity: 56 Gbps/336 Gbps	
Forwarding performance: 42 Mpps	
Memory(RAM): 512 MB	
Flash memory Hardware: 512 MB, of which 306 MB is available for users	
Operating Environment	
Temperature	Operation: -5°C ~ 50°C, Storage: -40°C ~ 70°C
Humidity	5 ~ 95%(Non-condensing)
Power Input	
Built-in AC	100 V AC to 240 V AC, 50/60 Hz
Dimension	
H x W x D	43.6 mm x 442 mm x 220 mm

SFP Module

Model	Specification
SFP-LX20	1.25Gbps SFP, SM, LC TYPE, 20km, 1310nm
SFP-SX	1.25Gbps SFP, MM, LC TYPE, 550m, 850nm