

# Gigabite PoE Optic Converter (SFP Slot Type)

10/100/1000Base-T 802.3af/at PoE 1-Ports + 1000Base-x SFP 1-Slot



- 10/100/1000Mbps TX 1Port(PoE) + 1000Base-X SFP 1Slot
- Supplies IEEE 802.3at Max 30W
- Operating Temperature -20°C~60°C
- DC 52V Input Power

SFC2000HP

## Specification

Standard	- Standard	IEEE 802.3 / 802.3u / 802.3ab, 10/100/1000 Base-T IEEE 802.3at pre-standard / 802.3af Power Over Ethernet Standard
Interface	- RJ45 Port	10/100/1000Mbps 1Port, Auto MDI/MDI-X UTP Cat5/5e/6 Cable EIA/TIA-568 Full or Half-duplex mode by Auto-Negotiation
	- Optical Port	1000Base-X, SFP 1-Slot Multi Mode : 62.5/125(2km) Single Mode : 9/125(20km ~ 100km)
	- LED	Power, FX Link/ACT, TP Link/ACT, PoE in Use
Specification	- Transmission Speed	1000Mbps
	- POE	DC47~57V, Max. 24 Watts
Operation Environment	- Temperature	Operating: 0°C ~ 60°C, Storage: -20°C ~ 80°C
	- Humidity	5 ~ 95% (non-condensing)
Input Power		DC 52V, 0.58A external AC-DC adapter
Dimension		70mm(W) x 95mm(D) x 26mm(H)

## Ordering Information

Model	Specification
SFC2000-HP	10/100/1000Base-TX(PoE) 1Port + 1000Base-FX SFP 1Slot
SFP-SX	SFP(1.25Gbps) Optic Module, Multi Mode, Transmission distance 220m, 850nm, LC Connector
SFP-SX2	SFP(1.25Gbps) Optic Module, Multi Mode, Transmission distance 2Km, 1310nm, LC Connector
SFP-LX	SFP(1.25Gbps) Optic Module, Single Mode, Transmission distance 20Km, 1310nm, LC Connector