

# 1G UTP 24Port + 10G SFP 4-Slot

10/100/1000Mbps UTP 24-Port + 1G/10G SFP -Slot



- 10/100/1000Mbps UTP 24-Port
- 1G/10G SFP 4-Port
- ERPS support
- Web based Management, SNMP Management
- IEEE 802.1p QoS, VoIP QoS, 1Q-in-Q function support
- 802.3ad Link Aggregation Control Protocol (LACP)
- Port Mirroring for Analysis of Network Errors and Traffics
- IEEE 802.1d & IEEE 802.1w Rapid Spanning Tree

## Product Specification

Technology	- Standard	IEEE 802.3 10Base-T IEEE 802.3ad Port trunk with LACP IEEE 802.1Q VLAN Tagging IEEE 802.3ae 10Gbps Ethernet	IEEE 802.3u/x/z 100Base-TX/FX, Gigabit SX/LX IEEE 802.1w Rapid spanning tree protocol IEEE 802.1x Port Authentication Network Control
	- RJ45 Ports	10/100/1000Mbps TP 24-Port, Auto-Negotiation, Auto MDI-X	
Interface	- Fiber Port	10G SFP 4-Slot, 10G SFP+ 1G/10G SFP	
	- LED Indication	System:Power Ports: 10/100/1000Mbps Link/Act/Speed, SFP Link	
Performance	- Back Plane	Switching Fabric 128Gbps, 16K MAC Address table, Jumbo Frame 9K	
	- Layer 2	Management Interfaces: Console, Telnet, Web Browser, SNMPv1, v2c, SNMP v3 VLAN: 802.1Q Tagged Based VLAN, Port VLAN, Q-in-Q, Private VLAN Edge (PVE) Spanning Tree: IEEE 802.1D, IEEE 802.1w Rapid Spanning Tree, IEEE 802.1s MSTP IEEE 802.3ad LACP / Static Trunk, IGMP (v1/v2/v3) Snooping IP-Based ACL / MAC-Based ACL, 802.1Q VLAN tag QoS	
Operating Environment	- Temperature	Operating: 0°C ~ 60°C, Storage: - 20°C ~ 80°C	
	- Humidity	5 ~ 95% (Non-condensing)	
Power Supply		100~240VAC, 50/60Hz	
Dimension		440mm(W) x 180mm(D) x 44mm(H), 1U	

## Ordering Information

Model Type	Specification
SFC4200T	10/100/1000Mbps UTP 24-Port + 1G/10G SFP -Slot
SFP+10G-LR	SFP(10G) module, Single-mode, Transmission Distance 10km, 1310nm, LC Connector
SFP-SX	SFP(1.25Gbps) module, Multi-mode, Transmission Distance 220/550m, 850nm, LC Connector
SFP-LX	SFP(1.25Gbps) module, Single-mode, Transmission Distance 20km, 1310nm, LC Connector