

PoE 16-Ports Gigabit Optical Switch

POE 10/100/1000Mbps TP 16-Ports + SFP 2-Slots (PoE 802,3at)



- 802.3af/at POE (Max. 260Watt)
- 10/100/1000Mbps TP 16-Ports
- FULL – duplex mode IEEE802.3x flow control
- 9216 bytes jumbo frame packet wire transmission
- 1000Mbps SFP 2-Slots

Specifications

Technology	Standard	IEEE 802.3 10Base-T IEEE 802.3 10Base –TX IEEE 802.3ab 1000Base-T IEEE 802.3af, IEEE802.3at
Interface	RJ45 Port	10/100/1000Mbps TP 16-Ports Auto-Negotiation, Auto MDI-X TP/STP Cat. 3,4,5 Cable EIA/TIA – 568 100-ohm(100m)
	SFP Slots	SFP 2-Slots 1000Mbps-SX/LX SFP
	LED Indication	Power, FD, Link/Act, Speed, PoE
Performance	PoE	POE Power Budget: Max. 260Watt Number of PD@30.8Watt / 8Port Number of PD@15.4Watt / 16Port
Operating Environment	Temperature	Operating: 0°C ~ 60°C, Storage: -20°C ~ 80°C
	Humidity	5 ~ 95% (Non-condensing)
Power Supply		100~240VAC, 50/60Hz
Dimension		440mm(W) x 205mm(D) x 44mm(H)

Ordering Information

Model Type	Specification
SFC516HP	10/100/1000Mbps TP 16포트(PoE 802.3at) + SFP 2-Slots
SFP-SX	SFP(1.25Gbps) module, Multi-mode, Transmission Distance 220/550m 850m, LC Connector
SFP-LX	SFP(1.25Gbps) module, Single-mode, Transmission Distance 20km, 1310nm, LC Connector