

# 16-slots Dual Power Gigabit Ethernet Fiber Optic Center

19 inch Standard Rack, 2U size, SFC2000 series Fiber Optic Converter Center, 16 Slots



- Standard 19" Rack Mounting Fiber Optic Center
- 16-slot mounting of Fiber Optic Converter
- AC Dual Power Support
- 16 Slot unit, 2 Power Supply
- 16 Slot Chassis for SFC2000 series

## Specification

<b>Standard</b>	- Standard	19 inch standard Rack, 2U size
<b>Interface</b>	- RJ45 Port	10/100/1000Mbps, Auto MDI/MDI-X UTP Cat3~6 Cable EIA/TIA-568 100-OHM (Transmission distance 100M)
	- Fiber Port	1000Mbps: 1-port, 1000Base-SX/LX/ZX (SC connector) Multi-mode: 62.5/125 $\mu$ m (220m) Single-mode: 9/125 $\mu$ m (~100km)
	- LED Indication	Power A. Power B
<b>Operation Environment</b>	- Temperature Range	Operation: - 0°C ~ 60°C, Storage: - 20°C ~ 80°C
	- Humidity	5 ~ 95% (Non-condensing)
	- Installation	19" RACK mount (2U)
<b>Input Power</b>		110VAC or 220VAC, 50/60Hz, Power redundant (Option)
<b>Dimension</b>		440.8mm(W) x 250mm(D) x 89mm(H)

## Ordering Guide

Model Type	Specification
<b>SFC CENTER/16G</b>	16 Slot unit, 1 Power Supply, SFC2000 Series, Gigabit Ethernet
<b>SFC CENTER/16GD</b>	16 Slot unit, 2 Power Supply, SFC2000 Series, Gigabit Ethernet, Dual Power